

TECHNICAL DATA SHEET

FINOPRIMER 765

Deep penetrating primer



Areas of application

Deep-penetrating primer designed to strengthen absorbent substrates. It reduces surface absorbency, improves adhesion of subsequent layers, and facilitates further finishing work. The product is part of the FINOCEM system. Ideal for substrates such as: ready-made putties, gypsum and cement-based putties, cement-lime and gypsum plasters, drywall boards, self-leveling screeds, cement and anhydrite floors and screeds (including those with underfloor heating).

Properties

- Deep-penetrating
- Reduces absorbency
- Frost-resistant
- Water-repellent

Application procedure



Technical data

Item number	42195	460997
Packaging		
Quantity per unit	1 L/unit	5 L/unit
Unit per pallet	12 Pack/carton	120 unit/Pal.
Consumption	approx. 0,2 L/m ²	
Drying time	≤ 4 h	

Material base

- Water dispersion of acrylic polymer
- Additives
- Water

FINOPRIMER 765

Deep penetrating primer

Application conditions

Use at temperatures from +5 °C to +25 °C; these temperatures refer to the air, substrate, and product. All substrates must be load-bearing, compact, stable, even, and clean.

Surface

Cement-lime plaster: in case of high absorbency, prime twice
Gypsum plasters: in case of high absorbency, prime twice
Gypsum plasterboard: prime once
Concrete, reinforced concrete: prime once
Screed: prime once
Symptoms of biological aggression must be eliminated.
Cracked and superficially scratched areas should be repaired and filled, for example, with mortar 428. The mortar in the repaired areas must be dry and well bonded.
Contaminants on the substrate such as greases, oils, and anti-adhesive agents must be completely washed off with water mixed with detergents. The substrate moisture content should not exceed 4%.

Preparation

Product ready to use. Do not dilute with water or mix with other materials. Thoroughly mix the contents of the package before use.

Application procedure

Apply the primer with a roller, brush, or spray method. Avoid excessive priming. During application and drying, protect from frost, precipitation, excessive heat, and strong wind.

Storage

Up to 12 months from the date of production in tightly sealed packaging and at a temperature between +5 °C and +25 °C, stored in a place inaccessible to children, protected from direct sunlight, away from sources of heat and open flames. Can be transported by any means of transport at

at temperature not lower than +5 °C. Not subject to ADR regulations.

General information

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.