



EXPERT grunt do ścian 317

Ready-to-use primer for cement-lime and gypsum plasters

Areas of application: Primer for gypsum and cement-lime plasters
Reinforces the groundwork, limits and evens out its absorbency without hindering its vapor-permeability.
Indoor and outdoor use

Properties:

- Ready to use
- Vapor-permeable
- Increases the adhesion of plasters, adhesives and grouts
- Facilitates plaster application
- Regulates groundwork absorbency
- Frost-resistant
- Waterproof

Application procedure:

Technical data	
Item no.	1
Packaging type	
Quantity per unit	15 kg
Unit per pallet	24 Pcs/pallet
Colour	yellow
Consumption	approx. 0.25 kg/m ²
Drying time	approx. 2 hours (temp. +20 °C)
Hardening time	approx. 12 hours

The product conforms to: • The product is not a construction product and does not require a reference document.

Material base:

- Additives
- Pigments
- Water
- Water dispersion of acrylic polymer

Surface: Contaminations of the substrate with greases, oils, and anti-adhesive agents should be completely washed off with water and detergents.
Repair all surface irregularities, cracks or cavities with material matching the groundwork. The mortar used in the repair sites must be dry and properly set.
Cover all surfaces not intended for priming before the primer is applied.

Types of substrate:

Bricks and ceramic CMUs: Apply directly
Wall of brick: Apply directly
Autoclaved aerated concrete elements: Apply directly
Silicate blocks: Apply directly
Expanded clay aggregate blocks: Apply directly

Application procedure: Primer, apply with a roller, brush or using spray application
Drying time in optimal conditions is minimum 2 hours

Application conditions: Apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean
Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.

Instructions: Do not mix with other solutions.



EXPERT grunt do ścian 317

Ready-to-use primer for cement-lime and gypsum plasters

Storage:

The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.

General information:

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing. All technical data is given for the temperature of 20 degrees Celsius. These temperatures apply to air, bed and embedded material.