



## GRUNTOLIT-SK 313

Primer for gypsum plasters, gypsum adhesives and anhydrite flooring grout.


**Areas of application:** Concentrated primer for final preparation of groundwork before the application of gypsum plasters and adhesives and anhydrite flooring grout. limits and evens out groundwork absorbency, facilitates the application of plasters, grouts and gypsum adhesives.

**Properties:**

- Waterproof
- Vapor-permeable
- Increases the adhesion of plasters, adhesives and grouts
- Facilitates the application of plasters, adhesives and grouts
- Regulates groundwork absorbency
- Concentrated

**Application procedure:**



Technical data	
Item no.	29029
Packaging type	
Quantity per unit	15 kg
Unit per pallet	24 Pcs/pallet
Colour	green
Consumption	approx. 0.12 kg/m <sup>2</sup>
Hardening time	approx. 12 hours
pH-value	approx. 7

**Material base:**

- Additives
- Pigments
- Water
- Water dispersion of acrylic polymer

**Surface:** All grease, oil, anti-adhesive stains must be thoroughly cleaned with water with detergents or with the RENO-BRUK 1003 solution. Repair all surface irregularities, cracks or cavities with material matching the groundwork. The mortar used in the repair sites must be dry and properly set. Cover all surfaces not intended for priming before the primer is applied.

**Types of substrate:**

**Concrete, reinforced concrete:** Dilute depending on the works performed

**Wall of brick:** Dilute depending on the works performed

**Old screed:** prime after diluting 1:1

**Moldy surfaces:** Clean with SEPTOBUD 1008 and then prime, maintaining the correct dilution ratio

**Groundwork with cracks or cavities:** Repair with mortar depending on groundwork type, and then prime, maintaining the correct dilution ratio

**Preparation:** Depending on the intended purpose, dilute with water in the following ratio: very absorbent groundwork 1:1 (G-SK:water), medium-absorbing 1:2, low-absorbing 1:3

**Application procedure:** Primer, apply with a roller, brush or using spray application  
Drying time in optimal conditions is minimum 2 hours

**Application conditions:** Apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean  
Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.

**Instructions:** Do not mix with other solutions.



## GRUNTOLIT-SK 313

Primer for gypsum plasters, gypsum adhesives and anhydrite flooring grout.

---

**Storage:**

The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.

---

**General information:**

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.

All technical data is given for the temperature of 20 degrees Celsius. These temperatures apply to air, bed and embedded material.