

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****Product identifier****Trade name:****SILICATE PAINT 002**

Silicate facade paint

**Relevant identified uses of the substance or mixture and uses advised against****Life cycle stages**

C/PW Consumer use / Widespread use by professional workers

**Sector of Use**

SU19 Building and construction work

**Product category**

PC9a Coatings and paints, thinners, paint removers

**Process category**

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC19 Manual activities involving hand contact

**Environmental release category**

ERC10a / ERC11a Widespread use of articles with low release

**Article category**

AC0 Other

**Application of the substance / the preparation**

Silicate paint - Product for an industrial, technical and private use for coating building surfaces. For all other uses is advised against/ not recommended.

**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**KREISEL - Technika Budowlana Sp. z o.o.  
ul. Szarych Szeregów 23  
60-462 Poznań  
Poland

Tel. +48 61 846 79 00

Fax +48 61 846 79 09

sekretariat@kreisel.pl

www.kreisel.pl

**Further information obtainable from:**

Bartosz Polaczyk - Tel.: +48 510 022 908, +48 61 84 67 966, bartosz.polaczyk@kreisel.pl

On working days 8 a.m. - 4 p.m.

**Emergency telephone number**

National poisons information centre: +44/(0)171 - 635 9191

National Health Service: 111

European emergency call: 112

**SILICATE PAINT 002**

(Contd. of page 1)

## SECTION 2: Hazards identification

### Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

### Label elements

GHS label elements Void

### Hazard pictograms

Void

### Signal word

Void

### Hazard statements

Void

### Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### Other hazards

No further relevant information available.

### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### Chemical characterization: Substances

This product is a mixture.

### Mixtures

### Description:

Mixture of polymer dispersion and water glass and nonhazardous fillers and additions.

### Dangerous components:

CAS: 13463-67-7 EINECS: 236-675-5 Index number:... 022-006-00-2 REACH: 01-2119489379-17	Titanium dioxide (<1% particles ≤ 10µm, Note 10)	5 - 10%
CAS: 1312-76-1 EINECS: 215-199-1 REACH: 01-2119456888-17	Silicic acid, potassium salt (M/M > 3,2) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 40 % Eye Irrit. 2; H319: C ≥ 40 % STOT SE 3; H335: C ≥ 75 %	2.5 - 5%

(Contd. on page 3)

**SILICATE PAINT 002**

(Contd. of page 2)

CAS: 12001-26-2 EC number: 601-648-2 REACH: <sup>1</sup>	Mica - Potassium aluminum silicate (Muscovite)	1 - 2.5%
CAS: 2634-33-5 EINECS: 220-120-9 Index number:... 613-088-00-6 REACH: 01-2120761540-60	1,2-benzisothiazol-3(2H)-one ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 ATE: LD <sub>50</sub> oral: 450 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.05 %	< 0.01%
<b>Other components (&gt;20%):</b>		
CAS: 7732-18-5 EINECS: 231-791-2 REACH: <sup>1</sup>	Water	25 - 50%
CAS: 1317-65-3 EINECS: 215-279-6 REACH: <sup>1</sup>	Limestone (Calcium carbonate) Consisting of: 471-34-1 Calcium carbonate (> 90%); 16389-88-1 Calcium/Magesium carbonate (0 - 10%); 14808-60-7 Quartz (SiO <sub>2</sub> ) (0 - 10%); 37244-96-5 Feldspar (0 - 5%); 12001-26-2 Mica - Potassium aluminum silicate (Muscovite) (0 - 5%)	25 - 50%

**Additional information:**

For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

<sup>1</sup> Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.

## SECTION 4: First aid measures

**Description of first aid measures**

First aid

**General information:**

For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

**After inhalation:**

Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contaminated shoes before reuse. If skin irritation continues, consult a doctor.

**After eye contact:**

Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

(Contd. on page 4)

**SILICATE PAINT 002**

(Contd. of page 3)

**After swallowing:**

Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control center.

**Most important symptoms and effects, both acute and delayed**

Symptoms and effects are described in section 2 and 11.

**Hazards:**

No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

If a physician is to be consulted, as per possibility he should be presented this safety data sheet.

**SECTION 5: Firefighting measures****Extinguishing media**

The mixture is flammable neither in the delivery condition nor in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

**Suitable extinguishing agents:**

The mixture is flammable neither in the delivery condition nor in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

**Special hazards arising from the substance or mixture**

This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

**Advice for firefighters**

No special measures required. Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures****Personal precautions, protective equipment and emergency procedures**

If appropriate, reference must be made to exposure controls and personal protection (see section 8).

**Environmental precautions**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**Methods and material for containment and cleaning up**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

(Contd. on page 5)

**SILICATE PAINT 002**

(Contd. of page 4)

**Information about fire - and explosion protection:**

No special measures required.

**Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

**Information about storage in one common storage facility:**

Keep away from foodstuffs, beverages and feed.

**Further information about storage conditions:**

Protect from frost. Protect from heat and direct sunlight.

**Minimum storage life:**

Minimum storage life (+5°C up to 25°C): See indication on package.

**Storage class:** 12**Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**Control parameters****Ingredients with limit values that require monitoring at the workplace:****13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)**

WEL (Great Britain)	Long-term value: 10* 4** mg/m <sup>3</sup> *total inhalable **respirable
---------------------	---

**12001-26-2 Mica - Potassium aluminum silicate (Muscovite)**

WEL (Great Britain)	Long-term value: 10* 0.8** mg/m <sup>3</sup> *total inhalable **respirable
---------------------	---

**DNELs****13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)**

Oral	Long term exposure	700 mg/kg bw/d (Consumer)
Inhalative	Systemic - Long term exposure	10 mg/m <sup>3</sup> (Employee)

**1312-76-1 Silicic acid, potassium salt (M/M > 3,2)**

Oral	Long term exposure	0.74 mg/kg bw/d (Consumer)
Dermal	Systemic - Long term exposure	0.74 mg/kg bw/d (Consumer) 1.49 mg/kg bw/d (Employee)
Inhalative	Systemic - Long term exposure	1.38 mg/m <sup>3</sup> (Consumer) 5.61 mg/m <sup>3</sup> (Employee)

**2634-33-5 1,2-benzisothiazol-3(2H)-one**

Dermal	Systemic - Long term exposure	0.345 mg/kg bw/d (Consumer) 0.966 mg/kg bw/d (Employee)
Inhalative	Systemic - Long term exposure	1.2 mg/m <sup>3</sup> (Consumer) 6.81 mg/m <sup>3</sup> (Employee)

**PNECs****13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)**

Freshwater	0.127 mg/l
Marine water	1 mg/l
Soil	> 100 mg/kg

(Contd. on page 6)

**SILICATE PAINT 002**

(Contd. of page 5)

Sediments (Freshwater)	> 1,000 mg/kg
Sediments (Marine water)	100 mg/kg
Sewage plant	100 mg/l
<b>1312-76-1 Silicic acid, potassium salt (M/M &gt; 3,2)</b>	
Freshwater	7.5 mg/l (not specified)
Marine water	1 mg/l (not specified)
Soil	mg/kg (not specified) no hazard identified
Sediments (Freshwater)	mg/kg (not specified) no hazard identified
Sediments (Marine water)	mg/kg (not specified) no hazard identified
Sewage plant	348 mg/l (not specified)
<b>2634-33-5 1,2-benzisothiazol-3(2H)-one</b>	
Freshwater	0.00403 mg/l (not specified)
Marine water	0.000403 mg/l (not specified)
Soil	3 mg/kg (not specified)
Sediments (Freshwater)	0.0499 mg/kg (not specified)
Sediments (Marine water)	0.000499 mg/kg (not specified)
Sewage plant	1.03 mg/l (not specified)

**Ingredients with biological limit values:**

Void

**Additional Occupational Exposure Limit Values for possible hazards during processing:****14808-60-7 Silicon dioxide (fine dust)**

BOELV (EU)	Long-term value: 0.1* mg/m <sup>3</sup> *respirable fraction
------------	---

**Additional information:**

The lists valid during the making were used as basis.

**Information about design of technical facilities**

No further data; see item 7.

**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the work place.

**Respiratory protection:**

Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

(Contd. on page 7)

**SILICATE PAINT 002**

(Contd. of page 6)

**Hand protection:**

Hand protection: Chemical resistant protective gloves according EN ISO 374

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skin-protecting agents is recommended. To avoid skin problems reduce the wearing of gloves to the required minimum.

**Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material:**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Polychloroprene (material thickness  $\geq 0.5$  mm ; breakthrough time  $\geq 480$  min.)

Nitrile rubber (material thickness  $\geq 0.35$  mm ; breakthrough time  $\geq 480$  min.)

Butyl rubber (material thickness  $\geq 0.5$  mm ; breakthrough time  $\geq 480$  min.)

Fluororubber (material thickness  $\geq 0.4$  mm ; breakthrough time  $\geq 480$  min.)

Neoprene (material thickness  $\geq 0.5$  mm ; breakthrough time  $\geq 480$  min.)

**Not suitable are gloves made of the following materials:**

Non-liquid-tight gloves made of fabric, leather or similar materials.

**Eye/face protection:**

In case of splash risk use tightly fitting safety goggles according to EN 166.

**Body protection:**

Protective work clothing

**Risk management measures:**

An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

**Environmental exposure controls**

Avoid release in the environment. Use the surplus or dispose it of properly.

**SECTION 9: Physical and chemical properties**

**Information on basic physical and chemical properties****General Information****Physical state**

Fluid

**Appearance:****Form:**

Fluid

(Contd. on page 8)

**SILICATE PAINT 002**

(Contd. of page 7)

<b>Colour:</b>	Different according to colouring
<b>Odour:</b>	Mild
<b>Odour threshold:</b>	Not safety relevant
<b>pH at 20 °C (68 °F)</b>	8 - 10
<b>Change in condition</b>	
<b>Melting point/freezing point:</b>	~ 0 °C (~ 32 °F) (ISO 3016)
<b>Boiling point or initial boiling point and boiling range</b>	100 °C (212 °F)
<b>Flammability</b>	Product is not flammable.
<b>Flash point:</b>	Not applicable
<b>Auto-ignition temperature:</b>	> 400 °C (> 752 °F) (DIN 51794)
<b>Decomposition temperature:</b>	> 825°C to CaO and CO <sub>2</sub>
<b>Oxidising properties:</b>	None
<b>Explosive properties:</b>	Product does not present an explosion hazard.
<b>Ignition temperature:</b>	Product is not selfigniting.
<b>Vapour pressure at 20 °C (68 °F):</b>	23 hPa (17.3 mm Hg)
<b>Density and/or relative density</b>	
<b>Density at 20 °C (68 °F):</b>	1.2 - 1.45 g/cm <sup>3</sup> (10.01 - 12.1 lbs/gal)
<b>Particle size</b>	
<b>Viscosity:</b>	
<b>Dynamic at 20 °C (68 °F):</b>	> 1,000 mPas (DIN 53019)
<b>Solubility</b>	
<b>Water:</b>	Fully miscible
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined
<b>Solids content:</b>	60 - 64 %
<b>Solvent content:</b>	
<b>Organic solvents:</b>	0 %
<b>VOC without water (EC):</b>	0.81 - 1.32 g/l
<b>VOC with water (EC):</b>	0.09 - < 0.44 g/l
<b>VOC with water (EC):</b>	0.008 - < 0.03 %

**Other information****Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

GB

(Contd. on page 9)



**SILICATE PAINT 002**

(Contd. of page 8)

### SECTION 10: Stability and reactivity

**Reactivity**

No dangerous reactions known.

**Chemical stability:**

The product is stable as long as it is stored properly and dry.

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**Possibility of hazardous reactions**

No dangerous reactions known.

**Conditions to avoid**

No further relevant information available.

**Incompatible materials**

No further relevant information available.

**Hazardous decomposition products**

No dangerous decomposition products known.

**Minimum storage life:**

Minimum storage life (+5°C up to 25°C): See indication on package.

**Additional information:**

No further relevant information available.

### SECTION 11: Toxicological information

**Information on hazard classes as defined in Regulation (EC) No 1272/2008**

The product was not investigated. The statement is derived from the properties of the single components.

**Acute toxicity:**

Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**1317-65-3 Limestone (Calcium carbonate)**

Oral	LD <sub>50</sub>	6,450 mg/kg (Rat) (RTECS Data)
------	------------------	--------------------------------

**13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)**

Oral	LD <sub>50</sub>	> 5,000 mg/kg (Rat) (OECD 425)
	Carcinogenicity	(Mouse) (ECHA Registration dossier) no effects observed

Dermal	LD <sub>50</sub>	> 5,000 mg/kg (Rabbit)
--------	------------------	------------------------

**1312-76-1 Silicic acid, potassium salt (M/M > 3,2)**

Oral	LD <sub>50</sub>	> 5,000 mg/kg (Rat)
------	------------------	---------------------

Dermal	LD <sub>50</sub>	> 5,000 mg/kg (Rat)
--------	------------------	---------------------

**2634-33-5 1,2-benzisothiazol-3(2H)-one**

Oral	LD <sub>50</sub>	450 mg/kg (ATE) 1,150 mg/kg (Mouse)
------	------------------	--

Dermal	LD <sub>50</sub>	597 mg/kg (Rat) > 2,000 mg/kg (Rat)
--------	------------------	--

(Contd. on page 10)

**SILICATE PAINT 002**

(Contd. of page 9)

**Other information (about experimental toxicology):****13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)**

Oral	OECD 414 (Prenatal Developmental Toxicity)	(Rat) no effects observed
Irritation of skin	OECD 404 (skin)	(Rabbit) not corrosive
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing
	OECD 421 (Reproduction screening test)	(Rat) no effects observed
<b>1312-76-1 Silicic acid, potassium salt (M/M &gt; 3,2)</b>		
Irritation of skin	OECD 404 (skin)	(Rabbit) slightly irritating
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritating
Sensitisation	OECD 406 (sensitization)	(Guinea pig) not sensitising

**On the skin:**

Based on available data, the classification criteria are not met.

**On the eye:**

Based on available data, the classification criteria are not met.

**Sensitization:**

Sensitising effect by skin contact is possible by prolonged exposure.

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity:**

Based on available data, the classification criteria are not met.

**Carcinogenicity:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity:**

Based on available data, the classification criteria are not met.

**Specific target organ toxicity - single exposure (STOT SE):**

Based on available data, the classification criteria are not met.

**Specific target organ toxicity - repeated exposure (STOT RE):**

Based on available data, the classification criteria are not met.

**Aspiration hazard:**

Based on available data, the classification criteria are not met.

**Practical experience**

No further relevant information available.

**General comments**

No further relevant information available.

**Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 11)

**SILICATE PAINT 002**

(Contd. of page 10)

**SECTION 12: Ecological information****Toxicity**

The product was not investigated. The statement is derived from the properties of the single components.

**Aquatic toxicity:****1317-65-3 Limestone (Calcium carbonate)**

LC <sub>50</sub> (96h)	> 100 mg/l (Rainbow trout - oncorhynchus mykiss) (OECD 203)
LC <sub>50</sub> (48h)	> 100 mg/l (Water flea - daphnia magna) (OECD 202)
EC <sub>50</sub>	> 14 mg/l (Algae - desmodesmus subspicatus) (OECD 201)
	> 1,000 mg/l (Activated sewage sludge) (OECD 209)

**13463-67-7 Titanium dioxide (<1% particles ≤ 10µm, Note 10)**

LC <sub>50</sub> (48h)	5.5 mg/l (Water flea - daphnia magna)
LC <sub>50</sub> (96h Marine water)	> 10,000 mg/l (Fish)
LC <sub>50</sub> (96h Freshwater) (static)	> 100 mg/l (Goldfish) (OECD 203)
EC <sub>50</sub> (48h)	> 1,000 mg/l (Water flea - daphnia magna) (ASTM Standard E729)
EC <sub>50</sub> (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)
EC <sub>50</sub> (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>50</sub> (7d)	> 100 mg/l (Lemna minor) (OECD 221)
NOEC (48h)	1 mg/l (Water flea - daphnia magna)
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magna) (OECD 202)
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219)
	Soil
NOEC (32d)	> 1 mg/l (Algae - scenedesmus quadricauda)
NOEC (8d)	> 1,000 mg/l (Zebrafish - danio rerio) (OECD 212)

**1312-76-1 Silicic acid, potassium salt (M/M > 3,2)**

LC <sub>50</sub> (48h)	> 146 mg/l (Fish - leuciscus idus)
EC <sub>50</sub>	> 146 mg/l (Water flea - daphnia)
EC <sub>0</sub>	> 348 mg/l (Bacteria - pseudomonas putidas)
EC <sub>50</sub> (72h)	207 mg/l /biomass (Algae scenedesmus subcapitatus)

**2634-33-5 1,2-benzisothiazol-3(2H)-one**

LC <sub>50</sub> (96h)	1.6 mg/l (Rainbow trout - oncorhynchus mykiss) (OECD 203)
EC <sub>50</sub> (48h)	3.27 mg/l (Water flea - daphnia magna)
	1.5 mg/l (Water flea - daphnia)
EC <sub>50</sub> (72h)	0.11 mg/l (Algae - selenastrum capricornutum) (OECD 201)
	2 mg/l (Algae scenedesmus subcapitatus)
EC <sub>50</sub> (16h)	0.4 mg/l (Pseudomonas putida)
EC <sub>10</sub> (72h)	0.04 mg/l (Algae - selenastrum capricornutum) (OECD 201)
NOEC (21d)	1.2 mg/l (Water flea - daphnia magna) (OECD 202)
NOEC (28d)	0.21 mg/l (Rainbow trout - oncorhynchus mykiss) (OECD 215)

**Persistence and degradability**

A part of the components is biodegradable.

**Degree of elimination:****2634-33-5 1,2-benzisothiazol-3(2H)-one**

Biodegradation	> 70 % (Activated sewage sludge) (OECD 303 A)
	> 90 % (not specified) (OECD 302 B)

(Contd. on page 12)

**SILICATE PAINT 002**

(Contd. of page 11)

**Bioaccumulative potential****2634-33-5 1,2-benzisothiazol-3(2H)-one**

Log Kow 0.7 (not specified) (OECD 117)

**Bioconcentration factor (BCF)****2634-33-5 1,2-benzisothiazol-3(2H)-one**

Bioconcentration factor (BCF) 6.95 (not specified) (OECD 305)

**Mobility in soil**

No further relevant information available.

**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**Other adverse effects**

No further relevant information available.

**Literature**

No further relevant information available.

**Ecotoxicological effects:**

No further relevant information available.


**Behaviour in sewage processing plants:****2634-33-5 1,2-benzisothiazol-3(2H)-one**

EC <sub>20</sub> (0,5h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>20</sub> (3h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>50</sub> (3h)	13 mg/l (Activated sludge organisms) (OECD 209)
OECD 302 B Zahn Wellens Test	90 % (Activated sludge organisms) (OECD 302)
OECD 303 A Activated Sludge Units	% (Rat)
	> 70 % (Activated sludge organisms) (OECD 303 A)

**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**SECTION 13: Disposal considerations****Waste treatment methods****Recommendation:**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**European waste catalogue**

08 01 12	Waste paint and varnish other than those mentioned in 08 01 11
15 01 02	Plastic packaging

(Contd. on page 13)

**SILICATE PAINT 002**

(Contd. of page 12)

08 01 12 for residues of the unprocessed product  
15 01 02 for the completely emptied packaging

**Uncleaned packaging**
**Recommendation:**

Disposal must be made according to official regulations.  
Recycle only completely emptied packaging.

**Recommended cleansing agents:**

Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

<b>UN number or ID number</b> ADR, ADN, IMDG, IATA	Void
<b>UN proper shipping name</b> ADR, ADN, IMDG, IATA	Void
<b>Transport hazard class(es)</b> ADR, ADN, IMDG, IATA Class	Void
<b>Packing group</b> ADR, IMDG, IATA	Void
<b>Environmental hazards</b> Marine pollutant:	No
<b>Special precautions for user</b>	Not applicable
<b>Maritime transport in bulk according to IMO instruments</b>	Not applicable
<b>UN "Model Regulation":</b>	Void

**SECTION 15: Regulatory information**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poisons Act**
**Regulated explosives precursors**

None of the ingredients is listed.

**Regulated poisons**

None of the ingredients is listed.

**Reportable explosives precursors**

None of the ingredients is listed.

**Reportable poisons**

1310-58-3	Potassium hydroxide	17% of total caustic alkalinity
1310-73-2	Sodium hydroxide	12% of total caustic alkalinity

**GHS label elements** Void

(Contd. on page 14)

### SILICATE PAINT 002

(Contd. of page 13)

**Hazard pictograms** Void**Signal word** Void**Hazard statements** Void**Directive (EU) 2012/18****Named dangerous substances - ANNEX I :**

None of the ingredients is listed.

**Biozide ingredients (528/2012/EG):**

Data based on recipe and information on the raw materials from the supply chain.

1,2-benzisothiazol-3(2H)-one	< 0.01%
2-Methyl-2H-isothiazol-3-one	< 0.00015%

**Classification according 2004/42/EG:**

IIA(a) 30 - This product contains &lt; 30 g/l VOC (see chapter 9)

IIA(c) 40 - this product contains &lt; 40 g/l VOC (see chapter 9)

**Other regulations, limitations and prohibitive regulations:**

·Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

·Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH)

·Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

·Regulation (EC) 1013/2006 on shipments of waste

**Chemical safety assessment**

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

**Reasons for changes:**

\* Data compared to the previous version altered.

**Relevant phrases:**

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

**Advice for instructions:**

Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

(Contd. on page 15)

**SILICATE PAINT 002**

(Contd. of page 14)

**Literature and the data sources:****Department issuing MSDS:**

Product safety department (+43/(0)5522-41646-0 / klaus.ritter@fixit-gruppe.com)

**Contact:**

Dr. Klaus Ritter

**Date of previous version:** 28.02.2023**Version number of previous version:** 11**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/Germany)

PBT: persistent, bioaccumulative and toxic properties

vPvB: very persistent, bioaccumulative properties

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

**Further information:**

The information in this safety data sheet describe the safety requirements of our product and is based on our current state of our knowledge. They provide no assurance of product quality. Existing laws, ordinances and regulations, including those that are not mentioned in this data sheet must be observed by the recipient of our products in their own responsibility.