

# DECLARATION OF PERFORMANCE (DOP)

**Product name**  
HASIT HASOLAN®

**Manufacturer**  
HASIT Trockenmörtel GmbH  
Landshuter Str. 30  
D-85356 Freising

**No of the declaration and unique identification code of the product type**  
183791/2

**System/s of AVCP:**  
System 4

**Product type**  
Standard mortar for plastering GP

## Declared performance

Important features	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1
Water absorption	Wc0	EN 998-1
Water vapour permeability	15/35 (Table value)	EN 998-1
Tensile adhesive strength	≥ 0,04 N/mm <sup>2</sup> for fracture patterns A, B or C	EN 998-1
Thermal conductivity	λ <sub>10,dry,mat</sub> ≤ 0,82 W/(m*K) in case of P=50% λ <sub>10,dry,mat</sub> ≤ 0,89 W/(m*K) in case of P=90% (tabulated values)	EN 998-1
Durability	NPD	EN 998-1
Dangerous substances	NPD	EN 998-1

The performance of the product identified in this statement is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer named in the declaration.

Signed for and on behalf of the manufacturer by:

**Management: Karl Minichmair & Christiane Stockinger**

Name and function

**Freising, 2025-03-12**

**This document was produced electronically and is valid without signature.**

Place and date of issue

Signature