

Revision: 27.10.2024

Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4)

# SECTION 1: Identification of the substance/mixture and of the company undertaking

### **Product identifier**

#### Trade name:

# HASIT PI 276 ÖKOSIL QUARZ

Silicate brush-on plaster interior/exterior

# Relevant identified uses of the substance or mixture and uses advised against

### Life cycle stages

C/PW Consumer use / Widespread use by professional workers

#### **Sector of Use**

SU19 Building and construction work

# Product category

PC9a Coatings and paints, thinners, paint removers

# **Process category**

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC19 Manual activities involving hand contact

# **Environmental release category**

ERC10a / ERC11a Widespread use of articles with low release

### **Article category**

AC0 Other

# Application of the substance / the preparation

Dispersion paint/ Latex paint - Product for an industrial, technical and private use for coating building surfaces. For all other uses is advised against/ not recommended.

# Details of the supplier of the safety data sheet

# Manufacturer/Supplier:

HASIT Trockenmörtel GmbH Landshuter Straße 30 85356 Freising Germany

Tel. +49 (0)8161 602 0 Fax +49 (0)8161 602-70400 zentrale.verwaltung@hasit.de hasit.de

# Further information obtainable from:

Product Safety Department (Mon-Thu 8 a.m. - 4 p.m., Fri 8 a.m. - 12 p.m.) Tel. +43(0)5522 41646 169 klaus.ritter@fixit-gruppe.com

# **Emergency telephone number**



National poisons information centre: +44/(0)171 - 635 9191 National Health Service: 111

European emergency call: 112



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 1)

# SECTION 2: Hazards identification

#### Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

#### Label elements

GHS label elements Void

# **Hazard pictograms**

Void

# Signal word

Void

#### **Hazard statements**

Void

#### Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-Methyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

# Other hazards

No further relevant information available.

#### Results of PBT and vPvB assessment

#### PBT:

This substance/mixture contains no components classified as persistent, bioaccumulative and toxic (PBT) at levels of 0.1% or higher.

#### vPvB:

This substance/mixture contains no components classified as very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SECTION 3: Composition/information on ingredients

#### **Chemical characterization: Substances**

This product is a mixture.

# **Mixtures**

# **Description:**

Mixture of binder dispersion, fillers and nonhazardous additions

(Contd. on page 3)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

		(Col	ntd. of page 2
Dangerous compor	nents:		
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022 REACH: 01-211948		Titanium dioxide (<1% particles ≤ 10µm, Note 10)	5 - 10%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613 REACH: 01-212076		1,2-benzisothiazol-3(2H)-one  Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317  ATE: LD₅₀ oral: 450 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥0.05 %	< 0.05%
CAS: 2682-20-4 EINECS: 220-239-6 REACH: 01-2120764	4690-50	2-Methyl-2H-isothiazol-3-one  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥0.0015 %	< 0.0015%
Other components	(>20%):		
CAS: 7732-18-5 EINECS: 231-791-2 REACH: 1	Water		25 - 50%
CAS: 14808-60-7 EINECS: 238-878-4 REACH: <sup>1</sup>	Consisting	xide (< 1% RCS) g of: 14808-60-7 Quartz (SiO₂); 14464-46-1 Cristobalite; ·3 Tridymite	10 - 25%

# Additional information:

For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m.

# SECTION 4: First aid measures

# Description of first aid measures



First aid

# General information:

For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

### After inhalation:

Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

# After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contamionated shoes before reuse. If skin irritation continues, consult a doctor.

(Contd. on page 4)

<sup>&</sup>lt;sup>1</sup> Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 3)

# After eye contact:

Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

#### After swallowing:

Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control center.

# Most important symptoms and effects, both acute and delayed

Symptoms and effects are described in section 2 and 11.

#### Hazards:

No further relevant information available.

#### Indication of any immediate medical attention and special treatment needed

If a physician is to be consulted, as per possibillity he should be presented this safety data sheet.

# SECTION 5: Firefighting measures

#### Extinguishing media

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

# Suitable extinguishing agents:

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

# Special hazards arising from the substance or mixture

This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

# Advice for firefighters

No special measures required. Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# SECTION 6: Accidental release measures

# Personal precautions, protective equipment and emergency procedures

If appropriate, reference must be made to exposure controls and personal protection (see section 8).

# **Environmental precautions**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

### Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 4)

# SECTION 7: Handling and storage

#### Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

# Information about fire - and explosion protection:

No special measures required.

# Conditions for safe storage, including any incompatibilities

# Storage:

# Requirements to be met by storerooms and receptacles:

Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

# Information about storage in one common storage facility:

Keep away from foodstuffs, beverages and feed.

### Further information about storage conditions:

Protect from frost. Protect from heat and direct sunlight.

# Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Storage class: 12 Specific end use(s)

No further relevant information available.

# SECTION 8: Exposure controls/personal protection

Control	parameters
---------	------------

13463-67-	7 Titanium dioxide (<1% part	icles ≤ 10µm, Note 10)	
WEL (Gre	at Britain) Long-term value: 10	* 4** mg/m³	
	*total inhalable **res	pirable	
DNELs			
13463-67-	7 Titanium dioxide (<1% part	icles ≤ 10μm, Note 10)	
Oral	Long term exposure	700 mg/kg bw/d (Consumer)	
Inhalative	Systemic - Long term exposur	e 10 mg/m³ (Employee)	
2634-33-5	1,2-benzisothiazol-3(2H)-one	)	
Dermal	Systemic - Long term exposur	e 0.345 mg/kg bw/d (Consumer)	
		0.966 mg/kg bw/d (Employee)	
Inhalative	Systemic - Long term exposur	e 1.2 mg/m³ (Consumer)	
		6.81 mg/m³ (Employee)	
2682-20-4	2-Methyl-2H-isothiazol-3-one	9	
Oral	Long term exposure	0.027 mg/kg bw/d (Consumer)	
	Short term exposure	0.053 mg/kg bw/d (Consumer)	
Inhalative	Local - Long term exposure	0.021 mg/m³ (Consumer)	
		0.021 mg/m³ (Employee)	
	Local - Short term exposure	0.34 mg/m³ (Consumer)	



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

	(Contd. of page 5)
	0.34 mg/m³ (Employee)
PNECs	
13463-67-7 Titanium diox	ride (<1% particles ≤ 10μm, Note 10)
Freshwater	0.127 mg/l
Marine water	1 mg/l
Soil	> 100 mg/kg
Sediments (Freshwater)	> 1,000 mg/kg
Sediments (Marine water)	100 mg/kg
Sewage plant	100 mg/l
2634-33-5 1,2-benzisothi	azol-3(2H)-one
Freshwater	0.00403 mg/l (not specified)
Marine water	0.000403 mg/l (not specified)
Soil	3 mg/kg (not specified)
Sediments (Freshwater)	0.0499 mg/kg (not specified)
Sediments (Marine water)	0.000499 mg/kg (not specified)
Sewage plant	1.03 mg/l (not specified)
2682-20-4 2-Methyl-2H-is	othiazol-3-one
Freshwater	0.00339 mg/l (not specified)
Soil	0.047 mg/kg (not specified)
Sediments (Marine water)	0.00339 mg/kg (not specified)
Sewage plant	0.23 mg/l (not specified)

#### Ingredients with biological limit values:

Void

### Additional information:

The lists valid during the making were used as basis.

# Information about design of technical facilities

No further data; see item 7.

# Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the work place.

# Respiratory protection:



Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

#### Hand protection:



Hand protection: Chemical resistant protective gloves according EN ISO 374

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material (Contd. on page 7)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 6)

on consideration of the penetration times, rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skin-protecting agents is recommended. To avoid skin problems reduce the wearing of gloves to the required minimum.

# Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

# For the permanent contact gloves made of the following materials are suitable:

Polychloroprene (material thickness  $\geq 0.5$  mm; breakthrough time  $\geq 480$  min.) Nitrile rubber (material thickness  $\geq 0.35$  mm; breakthrough time  $\geq 480$  min.) Butyl rubber (material thickness  $\geq 0.5$  mm; breakthrough time  $\geq 480$  min.) Fluororubber (material thickness  $\geq 0.4$  mm; breakthrough time  $\geq 480$  min.) Neoprene (material thickness  $\geq 0.5$  mm; breakthrough time  $\geq 480$  min.)

# Not suitable are gloves made of the following materials:

Non-liquid-tight gloves made of fabric, leather or similar materials.

### Eye/face protection:



In case of splash risk use tightly fitting safety goggles according to EN 166.

#### **Body protection:**



Protective work clothing

### Risk management measures:

An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

# **Environmental exposure controls**

Avoid release in the environment. Use the surplus or dispose it of properly.

# SECTION 9: Physical and chemical properties

# Information on basic physical and chemical properties

**General Information** 

Physical state Fluid

Appearance:

Form: Fluid
Colour: Whitish
Odour: Mild

Odour threshold: Not safety relevant

**pH at 20 °C (68 °F)** 9 - 11

(Contd. on page 8)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

#### HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 7)

Change in condition

Melting point/freezing point:  $\sim 0 \, ^{\circ}\text{C} \, (\sim 32 \, ^{\circ}\text{F}) \, (ISO \, 3016)$ 

Boiling point or initial boiling point and

boiling range 100 °C (212 °F)

**Flammability** Product is not flammable.

Flash point: Not applicable

Oxidising properties: None

**Explosive properties:** Product does not present an explosion hazard.

**Ignition temperature:** Product is not selfigniting. **Vapour pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

Density and/or relative density

**Density at 20 °C (68 °F):** 1.49 - 1.65 g/cm³ (12.43 - 13.77 lbs/gal)

Particle size

Viscosity:

**Dynamic at 20 °C (68 °F):** > 1,000 mPas (DIN 53019)

Solubility

Water: Fully miscible

Partition coefficient n-octanol/water (log

value)Not determinedSolids content:56 - 60 %VOC without water (EC):0.00 g/lVOC with water (EC):0.00 g/lVOC with water (EC):0.000 %

#### Other information

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void

Oxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoidDesensitised explosivesVoid

# SECTION 10: Stability and reactivity

# Reactivity

No dangerous reactions known.

(Contd. on page 9)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 8)

# Chemical stability:

The product is stable as long as it is stored properly and dry.

# Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

# Possibility of hazardous reactions

No dangerous reactions known.

#### Conditions to avoid

No further relevant information available.

# Incompatible materials

No further relevant information available.

# **Hazardous decomposition products**

No dangerous decomposition products known.

# Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

# Additional information:

No further relevant information available.

# **SECTION 11: Toxicological information**

# Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product was not investigated. The statement is derivated from the properties of the single components.

# Acute toxicity:

Based on available data, the classification criteria are not met.

LD/LC50 v	values relevant	for classification:
14808-60-	7 Silicon dioxid	e (< 1% RCS)
Oral	LD <sub>50</sub>	> 5,000 mg/kg (Rat)
Dermal	LD <sub>50</sub>	> 5,000 mg/kg (Rat)
13463-67-	7 Titanium diox	ide (<1% particles ≤ 10μm, Note 10)
Oral	LD <sub>50</sub>	> 5,000 mg/kg (Rat) (OECD 425)
	Carcinogenicity	(Mouse) (ECHA Registration dossier) no effects observed
Dermal	LD <sub>50</sub>	> 5,000 mg/kg (Rabbit)
2634-33-5	1,2-benzisothia	azol-3(2H)-one
Oral	LD <sub>50</sub>	450 mg/kg (ATE)
	1,150 mg/kg (Mouse)	
		597 mg/kg (Rat)
Dermal	LD <sub>50</sub>	> 2,000 mg/kg (Rat)
2682-20-4	2-Methyl-2H-is	othiazol-3-one
Oral	LD <sub>50</sub>	232 - 249 mg/kg (Rat) (OECD 401)
Dermal	LD <sub>50</sub>	242 mg/kg (Rat) (OECD 402)
Inhalative	LC <sub>50</sub> (4h)	0.05 mg/l (ATE)
	LC <sub>50</sub> (4h)	0.11 mg/l (Rat) (OECD 403)

(Contd. on page 10)



Revision: 27.10.2024

Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4)

# HASIT PI 276 ÖKOSIL QUARZ

		(Contd. of page
Other information	on (about experimental toxicology):	
14808-60-7 Silic	on dioxide (< 1% RCS)	
Irritation of skin	OECD 404 (skin)	(Rabbit) not irritant
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing
13463-67-7 Tital	nium dioxide (<1% particles ≤ 10μm, Note 1	0)
Oral	OECD 414 (Prenatal Developmental Toxicity)	(Rat) no effects observed
Irritation of skin	OECD 404 (skin)	(Rabbit) not corrosive
Irritation of eyes	OECD 405 (eye)	(Rabbit) not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse) not sensitizing
	OECD 421 (Reproduction screening test)	(Rat)
2682-20-4 2-Met	hyl-2H-isothiazol-3-one	
Oral	OECD 408 (Repeated dose oral toxicity 90d)	19 mg/kg bw/day (Rat)
Irritation of skin	OECD 404 (skin)	(Rabbit) corrosive
Sensitisation	OECD 406 (sensitization)	(Guinea pig) sensitizing

# **Primary irritant effect:**

### On the skin:

Based on available data, the classification criteria are not met.

#### On the eye:

Based on available data, the classification criteria are not met.

# Sensitization:

Sensitising effect by skin contact is possible by prolonged exposure.

Based on available data, the classification criteria are not met.

# Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

# Carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity:

Based on available data, the classification criteria are not met.

# Specific target organ toxicity - single exposure (STOT SE):

Based on available data, the classification criteria are not met.

# Specific target organ toxicity - repeated exposure (STOT RE):

Based on available data, the classification criteria are not met.

### Aspiration hazard:

Based on available data, the classification criteria are not met.

(Contd. on page 11)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 10)

# **Practical experience**

No further relevant information available.

# **General comments**

No further relevant information available.

Information on other hazards

# **Endocrine disrupting properties**

None of the ingredients is listed.

# **SECTION 12: Ecological information**

# **Toxicity**

The product was not investigated. The statement is derivated from the properties of the single components.

Aquatic toxicity:	
13463-67-7 Titanium dioxide	(<1% particles ≤ 10μm, Note 10)
LC <sub>50</sub> (48h)	5.5 mg/l (Water flea - daphnia magma)
LC <sub>50</sub> (96h Marine water)	> 10,000 mg/l (Fish)
LC <sub>50</sub> (96h Freshwater) (static)	> 100 mg/l (Goldfish) (OECD 203)
EC <sub>50</sub> (48h)	> 1,000 mg/l (Water flea - daphnia magma) (ASTM Standard E729
EC <sub>50</sub> (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)
EC <sub>50</sub> (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>50</sub> (7d)	> 100 mg/l (Lemna minor) (OECD 221)
NOEC (48h)	1 mg/l (Water flea - daphnia magma)
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magma) (OECD 202)
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219) Soil
NOEC (32d)	> 1 mg/l (Algae - scenedesmus quadricauda)
NOEC (8d)	> 1,000 mg/l (Zebrafish - danio rerio) (OECD 212)
2634-33-5 1,2-benzisothiazol	-3(2H)-one
LC <sub>50</sub> (96h)	1.6 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
EC <sub>50</sub> (48h)	3.27 mg/l (Water flea - daphnia magma)
	1.5 mg/l (Water flea - daphnia)
EC <sub>50</sub> (72h)	0.11 mg/l (Algae - selenastrum capricornutum) (OECD 201)
	2 mg/l (Algae scenedesmus subcapitatus)
EC <sub>50</sub> (16h)	0.4 mg/l (Pseudomonas putida)
EC <sub>10</sub> (72h)	0.04 mg/l (Algae - selenastrum capricornutum) (OECD 201)
NOEC (21d)	1.2 mg/l (Water flea - daphnia magma) (OECD 202)
NOEC (28d)	0.21 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 215)
2682-20-4 2-Methyl-2H-isoth	iazol-3-one
LC₅₀ (96h Marine water)	2.98 mg/l (Water flea - daphnia magma)
LC₅₀ (96h Freshwater)	0.934 mg/l (Water flea - daphnia magma)
LC <sub>50</sub>	4.77 mg/l (Fish) (OECD 203)
EC <sub>10</sub>	0.044 mg/l (Water flea - daphnia magma) (OECD 211)
	4.93 mg/l (Fish)
EC <sub>50</sub>	41 mg/l (Activated sewage sludge) (OECD 209)

(Contd. on page 12)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

Persistence and de	gradability
EC <sub>50</sub> (16h)	2.3 mg/l (Pseudomonas putida)
	0.103 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201)
	(Contd. of page 11)

# 'ersistence and degradabιιιτy

A part of the components is biodegradable.

Degree of elimination:
2634-33-5 1,2-benzisothiazol-3(2H)-one
Biodegradation > 70 % (Activated sewage sludge) (OECD 303 A)
> 90 % (not specified) (OECD 302 B)

# **Bioaccumulative potential**

# 2634-33-5 1,2-benzisothiazol-3(2H)-one

Log Kow 0.7 (not specified) (OECD 117)

# **Bioconcentration factor (BCF)**

#### 2634-33-5 1,2-benzisothiazol-3(2H)-one

Bioconcentration factor (BCF) 6.95 (not specified) (OECD 305)

#### Mobility in soil

No further relevant information available.

#### Results of PBT and vPvB assessment

#### PBT:

This substance/mixture contains no components classified as persistent, bioaccumulative and toxic (PBT) at levels of 0.1% or higher.

This substance/mixture contains no components classified as very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **Endocrine disrupting properties**

This substance/mixture does not contain components with endocrine disrupting properties according to the criteria of Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentrations of 0.1% or higher.

# Other adverse effects

No further relevant information available.

#### Literature

No further relevant information available.

# **Ecotoxical effects:**

No further relevant information available.

Behaviour in sewage processing p	plants:
2634-33-5 1,2-benzisothiazol-3(2H)	-one
EC <sub>20</sub> (0,5h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
EC <sub>20</sub> (3h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
EC₅₀ (3h)	13 mg/l (Activated sludge organisms) (OECD 209)
OECD 302 B Zahn Wellens Test	90 % (Activated sludge organisms) (OECD 302)
OECD 303 A Activated Sludge Units	% (Rat)
	> 70 % (Activated sludge organisms) (OECD 303 A)
2682-20-4 2-Methyl-2H-isothiazol-3	-one
EC <sub>20</sub> (3h)	2.8 mg/l (Activated sludge organisms) (DIN 38412-3 TTC-Test)
	(Contd. on page 13)

(Contd. on page 13)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

#### HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 12)

# Additional ecological information:

#### **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# SECTION 13: Disposal considerations

#### Waste treatment methods

#### Recommendation:





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Europea	n waste catalogue
08 01 12	Waste paint and varnish other than those mentioned in 08 01 11
15 01 02	Plastic packaging

08 01 12 for residues of the unprocessed product 15 01 02 for the completely emptied packaging

# **Uncleaned packaging**

#### Recommendation:

Disposal must be made according to official regulations.

Recycle only completely emptied packaging.

# Recommended cleansing agents:

Water, if necessary together with cleansing agents.

UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards		
Marine pollutant:	No	

(Contd. on page 14)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

#### HASIT PI 276 ÖKOSIL QUARZ

Special precautions for user

Not applicable

Maritime transport in bulk according to IMO instruments

Not applicable

UN "Model Regulation":

Void

# **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poisons Act** 

Regulated explosives precursors	
None of the ingredients is listed.	
Regulated poisons	
None of the ingredients is listed.	
Reportable explosives precursors	
7631-99-4 Sodium nitrate	Listed
Reportable poisons	
1310-58-3 Potassium hydroxide	17% of total caustic alkalinity

GHS label elements Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

**Directive (EU) 2012/18** 

Named dangerous substances - ANNEX I:

None of the ingredients is listed.

# Biozide ingredients (EU) 528/2012:

Data based on recipe and information on the raw materials from the supply chain.

1,2-benzisothiazol-3(2H)-one	< 0.05%
Tetramethylolacetylene diurea	< 0.03%
2-Methyl-2H-isothiazol-3-one	< 0.0015%

# Classification according (EU) 2004/42:

IIA(a) 30 - This product contains < 30 g/I VOC (see chapter 9)

#### Other regulations, limitations and prohibitive regulations:

·Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

·Commission Regulation (EU) No 878/2020 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (UK REACH)

(Contd. on page 15)



Version number: RO/ 5 (replaces version 4) Printing date 12.11.2024 Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 14)

- ·Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
- Regulation (EC) No 1013/2006 of the European Parliament and of the Council of 14 June 2006 on shipments of waste
- Regulation (EC) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products

### **Chemical safety assessment**

A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

### Reasons for changes:

\* Data compared to the previous version altered.

### Relevant phrases:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

# Advice for instructions:

Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

#### Literature and the data sources:

#### **Department issuing MSDS:**

Product safety department (+43/(0)5522-41646-0 / klaus.ritter@fixit-gruppe.com)

Dr. Klaus Ritter

# Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/ Germany)

PBT: persistent, bioaccumulative and toxic properties

vPvB: very persistent, bioaccumulatice properties

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 16)



Printing date 12.11.2024 Version number: RO/ 5 (replaces version 4) Revision: 27.10.2024

# HASIT PI 276 ÖKOSIL QUARZ

(Contd. of page 15)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

#### **Further information:**

The information in this safety data sheet describe the safety requirements of our product and is based on our current state of our knowledge. They provide no assurance of product quality. Existing laws, ordinances and regulations, including those that are not mentioned in this data sheet must be observed by the recipient of our products in their own responsibility.

- GF