

## TECHNICAL DATA SHEET

### FARBA ANTYPREFLEX 080

Anti-reflective interior paint



#### Areas of application

High-quality deep matt coating based on the highest quality components. Visually removes small imperfections in the surface structure, ideal for rough surfaces such as plaster, lime-cement plaster, plasterboard. Uniformly matt, regardless of the light angle. Perfect for large areas. Resistant to washing, scrubbing also non-aggressive detergents, disinfectants.

#### Properties

- Hides unevenness
- High resistance to washing and scrubbing
- Extra white
- Matt
- Splash-free
- Indoor use

#### Application procedure



#### Technical data

| Item number               | 39558                              | 39684        |
|---------------------------|------------------------------------|--------------|
| Packaging                 |                                    |              |
| Quantity per unit         | 2,5 L/unit                         | 10 L/unit    |
| Unit per pallet           | 80 unit/Pal.                       | 33 unit/Pal. |
| Colour                    | White                              |              |
| Consumption               | approx. 0,09 L/m <sup>2</sup>      |              |
| Resistant to wet scuffing | 1st degree (according to EN-13300) |              |
| sd-value                  | 0,14 m                             |              |
| Drying time               | approx. 2 h                        |              |

# FARBA ANTYREFLEX 080

Anti-reflective interior paint

## Material base

---

- Fillers
- Polymer dispersion
- Titanium dioxide
- Additives

## Application conditions

---

Apply in temperatures from +5 °C to +30 °C, these temperatures refer to air, groundwork and product temperature. Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.

## Surface

---

Depending on the absorbency and type of the substrate, prime with GRUNTOLIT-W 301 or GRUNTOLIT-SG 302. The type of priming method, substrate preparation should be checked before painting. Symptoms of biological aggression should be eliminated. Repair all surface irregularities, cracks or cavities with material matching the groundwork. The mortar used in the repair sites must be dry and properly set. Cover all surfaces which are not intended for painting before the application of primers The surface must be dry before painting.

Cement-lime plaster: Prime with GRUNTOLIT-SG 302 or EXPERT 5

Gypsum plaster: Prime with GRUNTOLIT-SG 302 or EXPERT 5

Gypsum plasterboards: Prime with GRUNTOLIT-SG 302 or EXPERT 5

Concrete, reinforced concrete: Prime with GRUNTOLIT-W 301 or EXPERT 6

Finishing coats: Prime with GRUNTOLIT-SG 302 or EXPERT 5

Old paint coats: Depending on the needs, do not prime or prime with GRUNTOLIT-SG 302

## Surface pre-treatment

---

Paint cement-lime plasters after a minimum of 28 days, gypsum plasters after a minimum of 14 days. Gypsum smoothing after a minimum of 3 days, polymeric after a minimum of 2 days of drying.

## Preparation

---

Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use.

## Application procedure

---

Apply the paint with a roller, brush or using a spray-application unit The paint can be sprayed with all types of painting units e.g.: GRACO, using LP517 nozzle

## Instructions

---

Ventilate the rooms during the execution of works, but protect the plaster against drafts causing excessive drying of the surface Paint in a continuous manner on one surface, do not allow any parts of the painted surface to dry out in the process to avoid visible lines Use paint from one production batch on one surface Apply the next layer after a minimum of 6 hours of drying of the previous layer Adverse conditions (high humidity, low temperature) can considerably extend the drying time. Clean tools with clean water immediately after finishing work.

## Storage

---

Up to 24 months from the date of manufacture. Keep dry and in the original packaging at a temperature of +5 °C to +25 °C.

## General information

---

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up

## **FARBA ANTYREFLEX 080**

Anti-reflective interior paint

with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.

All technical data listed in this product specification has been determined under laboratory conditions.