



TYNKOLIT-U 340

Universal primer for thin-layer plasters

Areas of application: Ready to use primer for mineral, acrylic, silicate, silicone, mosaic and other plasters. Limits and levels absorbency, reinforces the groundwork, facilitates painting and increases paint adhesion to the groundwork. It has a high covering power, which is important when applying plasters and when making scratched structures. The primer is also suitable for the mineral textured paint PAINT 071.

- Properties:**
- Increases groundwork adhesion
 - Universal
 - Good coverage capacity
 - For all types of plasters
 - With quartz addition
 - Regulates groundwork absorbency
 - Waterproof
 - Frost-resistant

Application procedure:



Technical data		
Item no.	34253	32713
Packaging type		
Quantity per unit	20 kg	7 kg
Unit per pallet	33 Pcs/pallet	80 Pcs/pallet
Colour	White	
Consumption	approx. 0.25 kg/m ²	
Drying time	about 4 hours under optimal conditions	
Hardening time (at approx. +20 °C)	approx. 24 hours	
pH-value	approx. 7	

The product conforms to:

- European Technical Assessment ETA 15/0576 and ETA 15/0575
- ETA 19/0198
- ICiMB-KOT-2017/0002

- Material base:**
- Quartz aggregate
 - Titanium white
 - Additives
 - Water
 - Polymer dispersion

Surface: Depending on the absorbency and type of groundwork, prime with GRUNTOLIT-W 301 or GRUNTOLIT-SG 302. Symptoms of biological aggression should be eliminated. Proceed to the execution of works after the dust settlement and groundwork drying period. After applying Lamella panels, proceed to priming after 24 hours (depending on ambient conditions). Cover all surfaces not intended for priming before the primer is applied.



TYNKOLIT-U 340

Universal primer for thin-layer plasters

Types of substrate:	Reinforcing layer in the thermal insulation system: without additional priming Cement-lime plaster: With high absorbency, prime with GRUNTOLIT-W 301 Cement plaster: without additional priming Gipsputz: Prime with GRUNTOLIT-W 301 or EXPERT 6 Gypsum plasterboards: Prime with GRUNTOLIT-SG 302 or EXPERT 5 Concrete: without additional priming Lamella wool: Apply directly Pre-primed lamella wool: Apply directly
Preparation:	Ready-to-use product. Do not dilute with water or mix with other materials. Mix thoroughly before use. It is recommended to use a plaster primer colored in the color of the plaster. This is particularly true for plaster with a scratched structure and intense colors.
Application procedure:	Primer, apply with a roller, brush or using spray application While performing works and during drying process, protect from frost, rainfalls, too high temperatures and strong winds.
Application conditions:	Apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.
Instructions:	When conducting works in adverse weather conditions, use special covers limiting the effects of external factors. Notice! The primer dye may slightly differ from the plaster dye, a plaster primer does not cover like paint does. Use the entire set of products in the thermal insulation system.
Storage:	The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.
General information:	This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.