KREISEL

TECHNICAL DATA SHEET

SEDIMENT REMOVER 1007

Solution for removing cement and lime sediment

Areas of application

Intended for non-aggressive removal of various types of cement and lime sediments For washing dirt and stains produced by water-borne minerals, rust, etc. For cleaning ceramic tiles and other, clinker bricks, chrome-plated elements, noble metal elements, plastic elements, and varnished elements. Indoor and outdoor use

Properties

- Environmentally friendly
- Easy to use
- Concentrated
- Removes saline efflorescence

Application procedure

Technical data

Item number	1409
Packaging	
Quantity per unit	1 L/unit
Unit per pallet	12 pcs./carton
Colour	colourless
Consumption	approx. 0,1 L/m^2
Density	approx. 1,05 g/cm^3 1,05 g/cm^3
pH value	1,5

Material base

- Organic tensides
- Water dispersion of citric acid

SEDIMENT REMOVER 1007

Solution for removing cement and lime sediment

Application conditions

Apply in temperatures above 0 °C

Application procedure

All cleaned surfaces should be moisted with water beforehand. Depending on the degree of dirt, the preparation should be diluted with water in accordance with the guidelines. Apply the product with a sponge or brush, rinse with plenty of water after the action. Strong dirt and durable deposits should be washed with the preparation several times or additionally, supporting the process mechanically with the use of a brush.

Instructions

Diluting with water: cement residue: from 1:3 to 1:5, for dirt or limestone residue: 1:5 to 1:10, for rust and water stains: from 1:10 to 1:15

Storage

The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.

General information

This product data sheet replaces all its previous versions.The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions.The product shall be applied in accordance with required technical knowledge and OHS rules.Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.
All technical data listed in this product specification has been determined under laboratory conditions.

Technical data sheet | EN | 07.08.2026