

## CE MARKING

**Product name**  
HASIT 706 OPTI

**Manufacturer**  
HASIT Trockenmörtel GmbH  
Landshuter Str. 30  
D-85356 Freising



### No of the declaration and unique identification code of the product type

|                                                                                                                       |                                                                                                                                                                                                      |          |
|-----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| 13                                                                                                                    |                                                                                                                                                                                                      |          |
| 231301                                                                                                                |                                                                                                                                                                                                      |          |
| EN 998-1                                                                                                              |                                                                                                                                                                                                      |          |
| Fine plaster mortar (CR)                                                                                              |                                                                                                                                                                                                      |          |
| Plaster mortar (P I, CS II) for use as exterior and interior plaster for walls, ceilings, pillars and partition walls |                                                                                                                                                                                                      |          |
| Reaction to fire                                                                                                      | A2-s1, d0                                                                                                                                                                                            | EN 998-1 |
| Water absorption                                                                                                      | Wc2                                                                                                                                                                                                  | EN 998-1 |
| Water vapour permeability                                                                                             | 15/35 (Table value)                                                                                                                                                                                  | EN 998-1 |
| Tensile adhesive strength                                                                                             | $\geq 0,08 \text{ N/mm}^2$ with A, B or C demolition type                                                                                                                                            | EN 998-1 |
| Thermal conductivity                                                                                                  | $\lambda_{10, \text{dry, mat}} \leq 0,61 \text{ W/(m}^{\circ}\text{K)}$ in case of P=50% $\lambda_{10, \text{dry, mat}} \leq 0,66 \text{ W/(m}^{\circ}\text{K)}$ in case of P=90% (tabulated values) | EN 998-1 |
| Durability                                                                                                            | NPD                                                                                                                                                                                                  | EN 998-1 |
| Dangerous substances                                                                                                  | NPD                                                                                                                                                                                                  | EN 998-1 |