



# Glass cloth reinforcing mesh

Accessories

**Areas of application:** For making the reinforcing layer in TURBO thermal insulation systems on foamed polystyrene or wool.

**Properties:**

- Waterproof
- Frost-proof
- Alkali-resistant

**Application procedure:**



Technical data		
Item no.	424982	315205
Packaging type		
Quantity per unit	50 m <sup>2</sup> /roll	
Length	50 m	
Width	100 cm	
Weight	160 g/m <sup>2</sup>	145 g/m <sup>2</sup>
Consumption	1 lfm/m <sup>2</sup>	
Yield	50 m <sup>2</sup> /unit	

**Material base:** • Fiberglass

**Application procedure:** Making the reinforced layer: mineral wool boards should be pre-smoothed with a thin layer of adhesive by pressing the trowel firmly. Apply the mortar to the surface of a polystyrene or mineral wool board, drag it with a notched trowel, apply a reinforcing mesh strip and level evenly until it is completely covered. Reinforcing mesh strips should be laid with an overlap of about 10cm. The layer reinforced with a single mesh should be 3-5mm thick.

**Application conditions:** Use in temperatures recommended for a given thermal insulation system. Avoid performing works in adverse conditions. In the case of high temperatures, rainfalls, wind, use protective meshes on scaffolding.

**General information:** This data sheet invalidates all previous editions. The content of this safety sheet represents our current knowledge and practical experience. It is only general information and does not result in any liability on the part of the manufacturer for the design and method of use. There may be differences and specific conditions of execution. The product is to be used in accordance with the required technical knowledge and in accordance with the occupational safety rules.