

## TECHNICAL DATA SHEET

---

### SEPTOBUD 1008

Biocide



#### Areas of application

---

Intended for removing microorganisms (algae, mold) on facades, plasters, etc. Also suitable for cleaning, disinfecting walls roofs, rustproof production devices, sanitary equipment, etc. Indoor and outdoor use

#### Material base

---

- Water
- Additives

#### Application conditions

---

Apply in temperatures from +5 °C to +25 °C, these temperature refer to air, groundwork and product temperature.

#### Preparation

---

Ready-to-use product. Do not dilute Do not add water or any other solutions, e.g. dyes or surfactants. Do not mix with dry or wet construction chemistry products. Protect against washing by precipitation.

#### Application procedure

---

Apply the product with a brush, roller or a machine-spray unit on the infected surface. Leave for 24 hours to eradicate the microorganisms, then wash, e.g. with a pressure washer. High-humidity weather facilitates the action of solution components. Rain, however, is undesirable (washes the solution off the surface). When disinfecting chemical tanks, production systems, spray the entire surface thoroughly and leave for 24 hours to dry. After this time, wash thoroughly. Remove deactivated microorganisms on

#### Properties

---

- Easy to use
- Effective

#### Application procedure

---



# SEPTOBUD 1008

Biocide

walls and roofs with a sharp brush or water pressure device. In order to completely remove biological aggression, it is recommended to use the product again. After re-application, wait a minimum of 24 hours. Only after this time can you prime, paint and apply plasters. Microorganisms must not be removed before using the preparation as this leads to their spread.

## Instructions

---

Do not add Septobud to paints, primers, etc.

## Storage

---

The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.

## General information

---

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing.

All technical data listed in this product specification has been determined under laboratory conditions.