

TECHNICAL DATA SHEET

FLEXIBLE FACADE BOARD

DECORATIVE FACADE BOARD



Areas of application

Characterized by faster binding, compared to standard flooring base Reinforced with a reinforcing mesh After painting with the ACRYLIC AZURE1003, it is possible to achieve different colour variants.

Properties

- High elasticity
- Natural wood pattern
- Easy to install
- Waterproof
- Frost-proof

Application procedure



Technical data

| | |
|-------------------|--------------------------|
| Item number | 34877 |
| Packaging | |
| Quantity per unit | 24 Pack/carton |
| Unit per pallet | 10 unit/Pal. |
| Colour | White |
| Consumption | 3,87 Stk./m ² |
| Length | 2000 mm |
| Width | 128 mm |
| Thickness | 2 mm |

FLEXIBLE FACADE BOARD

DECORATIVE FACADE BOARD

Material base

- Fillers
- Mesh of glass fibre
- Polymers

Application conditions

While fixing and painting, apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product.

Surface

Substrates should be free from dust, soot, grease, lubricants, anti-adhesive agents, paints, excess mortar etc. Symptoms of biological aggression (fungi, mildew) should be removed using SEPTOBUD 1008 preparation. Old, destroyed coatings with low strength must be removed. Prime weak beds with GRUNTOLIT-SG 302
Reinforcing layer in the thermal insulation system: without additional priming
Concrete: Prime with TYNKOLIT-T 330 or TYNKOLIT 340
Cement-lime plaster: Prime with GRUNTOLIT-W 301 or EXPERT 6
Old plasters: Prime with GRUNTOLIT-SG 302 or EXPERT 5

Application procedure

In the case of thermal insulation system, the plank must be fixed directly to styrofoam or well-set reinforced layer (min. after 3 days) or to another stable bed e.g. plaster. Fix by means of the DISPERSION ADHESIVE 111. With regard to this adhesive, it is necessary to observe the minimum drying temperature which is +10 °C. It is possible to fix by means of a cement, white adhesive, etc.: EXPERT 2 WHITE, EXPERT 4. After min. 48 from fixing, the plank must be covered carefully with facade paint if necessary (e.g. ACRYLIC PAINT 001). 24 hours from painting, it must be carefully covered with Acrylic azure 1003 in a chosen colour along the grains using a brush. To achieve the rustic effect, directly after application, the scumble shall be wiped delicately with a clean, dry sponge. It is possible to apply the scumble twice, depending on the required effect While working on corners, DISPERSION ADHESIVE 111 must be used to finish the plank edges

General information

This data sheet invalidates all previous editions. The information in this technical data sheet corresponds to our current knowledge and practical application experience. The information has been prepared carefully and conscientiously, but without guarantee for accuracy, timeliness, and completeness, and without liability for further decisions of the user. The information alone does not establish any legal relationship or other ancillary obligations. They do not absolve the customer from the obligation to independently verify the suitability of the product for the intended use. Technical values refer to the base products. Deviations from the technical specifications may occur due to tinting and coloring. The specified values are average values. For coating substrates not described here, it is necessary to consult with us. Color tones may slightly vary in repeat orders or compared to the color chart, if necessary, a sample area should be created on-site. Information on drying and waiting times applies under laboratory conditions (+20°C/65% relative humidity) and may change depending on the site situation. All technical data listed in this product specification has been determined under laboratory conditions.