

DECLARATION OF PERFORMANCE (DOP)

Product name

HASIT 715

No of the declaration and unique identification code of the product type

440187

Product type

Fine plaster mortar CR

Intended use

Plaster mortar (P I, CS II) for use as exterior and interior plaster for walls, ceilings, pillars and partition walls

Manufacturer

HASIT Trockenmörtel GmbH • Landshuter Str. 30 • D-85356 Freising

System/s of AVCP:

System 4

Declared performance

Important features	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1:2016
Water absorption	W_c2	
Water vapor permeability (μ)	≤ 20	
Tensile adhesive strength	$\geq 0,08 \text{ N/mm}^2$ with A, B or C demolition type	
Thermal conductivity (tabulated value)	$\lambda_{10, \text{dry, mat}} \leq 0,61 \text{ W/mK}$ for P=50% $\lambda_{10, \text{dry, mat}} \leq 0,66 \text{ W/mK}$ for P=90%	
Durability	NPD	
Dangerous substances	NPD	

Performance of the above product corresponds to the specified performance(s). The manufacturer identified above is solely responsible for issuing the declaration of performance according to Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:

Name and function

Freising, 2021-06-21

Place and date of issue

This document was produced electronically and is valid without signature.

Signature