

## TECHNICAL DATA SHEET

### REMONT PRIMER 950

Specialist, siliceous priming agent



#### Areas of application

A primer based on water glass, intended for preparation of substrate before application of plasters, putties, gypsum finish, paints. Reinforces the groundwork, limits and evens out its absorbency without hindering its vapor-permeability. Perfect for silicate paints.


#### Properties

- Vapor-permeable
- Crystalline tie with the groundwork
- Regulates groundwork absorbency
- Frost-resistant
- Waterproof

#### Application procedure



#### Technical data

Item number	36183
Packaging	
Quantity per unit	5 L/unit
Unit per pallet	120 unit/Pal.
Colour	colourless
Consumption	approx. 0,175 L/m <sup>2</sup>
Possibilities to enter	approx. 12 h
Drying time	approx. 2 h

# REMONT PRIMER 950

Specialist, siliceous priming agent

## Material base

---

- Potassium water glass
- Polymers
- Water
- Additives

## Application conditions

---

Apply at temperatures from +5 °C to +25 °C, these temperatures apply to air, bed and product. All substrates shall be bearing, compact, stable, even and clean. Groundwork must be cleared from dust, grease, anti-adhesive solutions, paint residue, mold, algae, moss, etc., free from cracks and saline efflorescence.

## Surface

---

Symptoms of biological aggression should be eliminated. Repair all surface irregularities, cracks or cavities with material matching the groundwork. The mortar used in the repair sites must be dry and properly set. Cover all surfaces not intended for priming before the primer is applied.

Old plasters: double prime

Cement-lime plaster: prime once

screed: prime once

Gypsum plasters: Incompatible

OSBs, chipboards, fiberboards: Incompatible

Poor-quality, flaking wall joints.: double prime

Wall of brick: prime once

## Preparation

---

Ready-to-use product. Do not dilute

## Application procedure

---

Apply the agent with a roller, brush or by means of spraying. The average drying time is 12 hours. Protect against precipitation, direct sun rays, wind and frostbites during application and drying. Avoid excessive priming

## Instructions

---

When conducting works in adverse weather conditions, use special covers limiting the effects of external factors.

## Storage

---

The mortar can be stored for up to 12 months from production date in sealed packaging and at temperatures, ranging from +5 °C to +25 °C. The storage area shall be kept out of the reach of children, protected against direct sunlight and located far from heat sources and naked flames. It can be transported by any means of transport, at a temperature not lower than +5 °C. It is not subject to ADR provisions.

## General information

---

This product data sheet replaces all its previous versions. The information, included in this technical card, represents our current knowledge and practical experience. This is general information only which shall not obligate the manufacturer to take any responsibility either for workmanship or for the manner of use. For there may be differences and specific execution conditions. The product shall be applied in accordance with required technical knowledge and OHS rules. Avoid contact with skin and protect eyes. In case of contact with eyes, rinse them up with a large quantity of clean water and consult a doctor. It shall be recommended to use gloves, safety goggles and protective clothing. All technical data is given for the temperature of 20 degrees Celsius. These temperatures apply to air, bed and embedded material.

All technical data listed in this product specification has been determined under laboratory conditions.