

DECLARATION OF PERFORMANCE (DOP)

Product name
HASIT 710

Intended use
Plaster mortar (P I, CS II) for use as exterior and interior plaster for walls, ceilings, pillars and partition walls

No of the declaration and unique identification code of the product type
183771/1

Manufacturer
HASIT Trockenmörtel GmbH
Landshuter Str. 30
D-85356 Freising

Product type
Fine plaster mortar (CR)

System/s of AVCP:
System 4

Declared performance

Important features	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1
Water absorption	Wc2	EN 998-1
Water vapour permeability	5/20 (Table Value)	EN 998-1
Tensile adhesive strength	$\geq 0,08 \text{ N/mm}^2$ with A, B or C demolition type	EN 998-1
Thermal conductivity	$\lambda_{10, \text{dry, mat}} \leq 0,45 \text{ W/(m}^{\circ}\text{K)}$ for P=50% $\lambda_{10, \text{dry, mat}} \leq 0,49 \text{ W/(m}^{\circ}\text{K)}$ for P=90% (table value)	EN 998-1
Durability	NPD	EN 998-1
Dangerous substances	NPD	EN 998-1

The performance of the product identified in this statement is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer named in the declaration.

Signed for and on behalf of the manufacturer by:

Management: Karl Minichmair & Christiane Stockinger

Name and function

Freising, 2022-11-09

This document was produced electronically and is valid without signature.

Place and date of issue

Signature