

DECLARATION OF PERFORMANCE (DOP)

Product name
HASIT 250 RENOPLUS®

No of the declaration and unique identification code of the product type
183798/1

Product type
Standard mortar for plastering GP

Intended use
Plaster mortar CS II for use as exterior and interior plaster for walls, ceilings, pillars and partition walls

Manufacturer
HASIT Trockenmörtel GmbH • Landshuter Str. 30 • D-85356 Freising

System/s of AVCP:
System 4

Declared performance

Important features	Performance	Harmonised technical specification
Reaction to fire	A1	EN 998-1
Water absorption	$W_c 0$	
Water vapour permeability	15/35 (Table value)	
Tensile adhesive strength	$\geq 0,8 \text{ N/mm}^2$ bei Bruchbild A, B oder C	
Thermal conductivity	$\lambda_{10, \text{dry, mat}} \leq 0,61 \text{ W/(m}^*\text{K)}$ in case of P=50% $\lambda_{10, \text{dry, mat}} \leq 0,66 \text{ W/(m}^*\text{K)}$ in case of P=90% (tabulated values)	
Durability	NPD	
Dangerous substances	NPD	

Performance of the above product corresponds to the specified performance(s). The manufacturer identified above is solely responsible for issuing the declaration of performance according to Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:

Name and function

Freising, 2024-11-06

Place and date of issue

This document was produced electronically and is valid without signature.

Signature